

RG20

384# PET SPECIALTY FILAMENT TAPE

DESCRIPTION

A clear, fiberglass reinforced, polyester backed, strapping tape with a pressure-sensitive natural rubber /resin adhesive. High tensile strength, high adhesion and medium impact strength. Will not stain and will not impart odor or taste. Recommended shelf life: 6 months.

PRODUCT APPLICATION

Used in the appliance industry for securing components where direct contact with the surface of appliances is a factor. Not recommended for corrugated surfaces.

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Polyester Film
Adhesive	Natural Rubber / Resin
Reinforcement	Fiberglass
Adhesion to Steel (oz/in of width) (at 90 degrees peel angle)	43 (11.7 N/25mm)
Tensile Strength (lbs/in of width)	384 (1680 N/25mm)
Elongation (at break)	4%
Total Thickness (mils)	9.5 (0.24 mm)
Quick Stick (oz/in of width)	
To Kraft	6 (1.6 N/25mm)
To Steel	28 (7.6 N/25mm)
Color	Clear



3647 Cortez Road West | Bradenton, FL 34210 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 07/10

