

RP24

265# PET SPECIALTY FILAMENT TAPE

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

Uni-directional polyester strapping tape with reinforcements and a pressure-sensitive natural rubber adhesive. Excellent adhesion and exceptional shear strength.

PRODUCT APPLICATION

Packaging of large appliances where carton lift flap must support the weight of one or more appliances (not to exceed 9 lbs per square inch of tape). Also for steel and aluminum coil tabbing, packaging and carton closure.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	1.42 Ga. Polyester Film
Adhesive	Natural Rubber / Resin
Adhesion to Steel (oz/in of width) (at 90 degrees peel angle)	42 (11.5 N/25mm)
Tensile Strength (lbs/in of width)	265 (1160 N/25mm)
Elongation (at break)	27%
Total Thickness (mils)	10.2 (0.26mm)
Quick Stick (oz/in of width) To Kraft To Steel	3.5 (0.96 N/25mm) 26 (7.1 N/25mm)
Color	Natural



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 07/10

