



WATERPROOFING REPAIR TAPE



Backing:	Aluminum Foil
Adhesive:	Butyl Rubber
Liner:	Blue Polyethylene Film
Colors:	Aluminum
Specifications:	Tested in accordance with UL 723
Standard Sizes:	48mm x 10M

Applications

- Seals cracks and seams in gutters, roof alleys, eaves, hips and ridges
- Repair gouges, rips and tears in metal panels of trailers, shipping containers and metal buildings
- Sealing leaking pipes & hoses
- Permanent waterproofing and sealing applications

Features

- Aluminum Foil Backing
- Butyl Rubber Adhesive

Benefits

- Tough and durable
- Resists UV exposure outdoors
- Conformable & paintable
- Forms an instant air-tight and waterproof bond
- Permanent
- Non-Staining
- Excellent resistance to cold and hot conditions

Physical Properties

	Standard UOM	Metric UOM	Test Method
Total Thickness	11 mils	279.4 mic	ASTM D-1000
Adhesion to Steel	75 oz/in	8.21 N/cm	PSTC-101
Tensile Strength	20 lb/in	35.03 N/cm	ASTM D-1000
Operating Temperature	40 - 200° F	4 - 93° C	

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F
Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.