



**PATCO® 570**  
Colored Polyethylene Clean  
Room Tape


**APPLICATIONS**

- Excellent for color coding, sealing of clean room containers, identification of products and packaging materials.
- Suitable for splicing plastic films and as a surface and label overlamine.

**FEATURES & BENEFITS**

- Low in halogens and leachable chlorides.
- Minimizes contamination - replaces the use of potentially contaminating PVC vinyl tapes.
- Clean removal.
- Excellent conformability.
- Hand-tearable.

**CONSTRUCTION**



**PRODUCT DESCRIPTION**

**Single-Coated Construction**

**Backing:**

- Low Density Polyethylene

**Adhesive:**

- Acrylic

**Colors:**

- Blue, Green White, Tinted Orange

**TEST DATA**

Test	Typical Value	Typical Value (Metric)	Test Method
Total Thickness	5.5 mils	0.140 mm	PSTC-133
Substrate Thickness	4.5 mils	0.114 mm	PSTC-133
Adhesion to Steel	30 oz./in.	0.328 N/mm	ASTM D-3330
Tensile Strength	11 lb./in.	1.926 N/mm	ASTM D-3759
Elongation (%)	550 %		
Application Temperature Range	50°F to 120°F	10°C to 49°C	
Operating Temperature Range	-40°F to 190°F	-40°C to 88°C	

**\*\*Recommended storage conditions: 40-60% Humidity, 60 °F - 80 °F**

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.