

# tesa® 4563

Silicone rubber coated fabric tape with outstanding grip properties

## PRODUCT INFORMATION

### Product Description

tesa® 4563 consists of a specially treated fabric covered with a silicone rubber coating. This surface is highly resistant to "sticky" substances yet provides a reliable "non-slip" effect on smooth substrates. Non-slip properties are maximized by the smooth surface.

### Main Application

tesa® 4563 is specially designed for roller wrapping applications. In many cases, a new covering may be applied without removing the roller from the machine.

Industries include:

- Printing industry
- Textiles industry
- "Focus" label printing machinery
- General, web-based processing & converting industries

### Technical Data

|                     |                        |                      |                   |
|---------------------|------------------------|----------------------|-------------------|
| ■ Adhesion to steel | 4.1 N/cm<br>37.5 oz/in | ■ Type of adhesive   | natural rubber    |
| ■ Backing material  | Silicone-coated cloth  | ■ Type of liner      | PP                |
| ■ Surface texture   | smooth                 | ■ Thickness of liner | 80 µm<br>3.1 mils |
| ■ Total thickness   | 340 µm<br>13.4 mils    |                      |                   |

### Additional Info

The product's shelf life is 12 months.

4563 PV2 - Here the only difference compared to the PV0 is the adhesion to steel of 3,2N/cm

### tesa tape, inc.

5825 Carnegie Boulevard  
Charlotte, NC 28209  
Phone: 704 554 0707  
Toll Free: 800 426 2181  
Fax: 800 852 8831  
customer@tesatape.com

### Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170  
German Centre P 6-3-3Col.  
Lomas de Santa Fe  
Mexico D.F. C.P. 01210  
Phone: +52 (55) 5292 6978  
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.