

TAPE PRODUCTS TECHNICAL DATA

ACRYLIC REMOVABLE ASI TRANSFER TAPE

DESCRIPTION:

This is a brand new addition to our line of Pressure Sensitive Transfer Tapes which offer significant performance advantages over standard rubber based transfer adhesives.

PHYSICAL CHARACTERISTICS:

Adhesive Thickness: 1.0 MIL (+/- 0.2 MILS)

Liner Thickness: 2.5 MILS (+/- 0.2 MILS)

Total Product Thickness: 3.5 MILS (+/- 0.4 MILS)

TYPICAL TEST DATA:

180 Degree Peel (PSTC #3) 60 Gm./In.

APPLICATIONS:

- Great Heat resistance.
- Great chemical and plasticizer resistance.
- High shear holding power.
- Excellent UV resistance.
- User/Converter friendly - Virtually no adhesive build-up on blades during converting operation over a long period of time thus increasing production efficiencies.
- Good Clarity
- Clean removability from a variety of substrates

APPLICATION CONDITIONS:

40° F - 105° F (Surface must be clean and dry.)

SERVICE CONDITIONS:

-4° F - 200° F

STORAGE CONDITIONS:

50% Humidity at 77° F

SHELF LIFE: 1 Year