

# TAPE PRODUCTS TECHNICAL DATA

## **RUBBER BASED PERMANENT TRANSFER TAPE**

### **DESCRIPTION:**

A permanent adhesive on a differential silicone coated liner. The liner is a densified paper that affords an easy release from the adhesive film.

### **PHYSICAL CHARACTERISTICS:**

Adhesive Thickness:.....0.9 MILS (+/- 0.2 MILS)  
Liner Thickness:.....2.4 MILS (+/- 0.2 MILS)  
Total Product Thickness:.....3.3 MILS (+/- 0.4 MILS)

### **TYPICAL TEST DATA:**

180 Degree Peel (PSTC #3).....3000 grams/inch - 105 oz/inch  
Loop Tack.....3600 grams/square inch 126 oz/sq. in.  
Shear Strength (PSTC #7, 1000g).....48+ hours

### **APPLICATIONS:**

This product is commonly applied to posters, labels and business forms when a permanent bond is required. This product will not bleed on lightweight materials.

### **APPLICATION CONDITIONS:**

40 F - 105 F  
Surface must be clean and dry

### **SERVICE CONDITIONS:**

0 F - 140 F

### **STORAGE CONDITIONS:**

50% Humidity at 77 F

**SHELF LIFE:** 1 Year