

tesa® 51930

Aggressive Double-Sided Polyurethane Tape for Permanent Mounting

PRODUCT INFORMATION

Product Description

tesa® 51930 is a gray, polyurethane foam tape with a weather and age resistant acrylic adhesive, guaranteeing a secure, long-term bond for indoor or outdoor applications. It is highly resistant against fuel and other chemicals and offers high adhesion values.

tesa® 51930 has excellent shear properties and features a green polyethylene liner for easy, one-piece removal. It is used in applications where high adhesion as well as thickness is required. Available Colors: Gray

Main Application

- Bonding of display elements
- Bonding of signs and letters to walls, both inside and outside
- Bonding of trim to a variety of substrates, both smooth and rough

Technical Data

■ Backing material	PU foam	■ Type of adhesive	acrylic
■ Total thickness	812.8 µm 32 mils	■ Type of liner	PE

Adhesion to

■ Steel (initial)	10.9 N/cm 99.6 oz/in
-------------------	-------------------------

tesa tape, inc.

5825 Carnegie Boulevard
Charlotte, NC 28209
Phone: 704 554 0707
Toll Free: 800 426 2181
Fax: 800 852 8831
customer@tesatape.com

Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170
German Centre P 6-3-3Col.
Lomas de Santa Fe
Mexico D.F. C.P. 01210
Phone: +52 (55) 5292 6978
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.