

## PM2

### TAN MEDIUM GRADE PAPER FLATBACK TAPE

#### DESCRIPTION

A quick, sure sealing, economical, pressure-sensitive flatback tape which can increase packaging line efficiency. PM2 offers a positive attractive seal and excellent adhesion to discourage pilfering. Performs well under a wide range of temperatures through a wide range of humidity conditions. Offers the advantages of a balance of high quick stick and excellent holding properties. Performs well as a low temperature splicing tape and meets USPS requirements. Product is not repulpable.

#### PRODUCT APPLICATIONS

Can be used on all types of cartons.

#### GOVERNMENT COMPLIANCE

ASTM D6123, Type II

PPP-T-42C, Type II

C.I.D. A-A-883B Type II

Boeing BAC 5317



3647 Cortez Road West | Bradenton, FL 34210 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
[www.itape.com](http://www.itape.com) | [info@itape.com](mailto:info@itape.com)

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 03/11

## INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

#### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

<b>Backing</b>	Kraft Flatback Paper
<b>Adhesive</b>	Natural Rubber / Resin
<b>Adhesion to Steel</b> (oz/in of width) PSTC-101	57 (15.6 N/25mm)
<b>Tensile Strength</b> (lbs/in of width) PSTC-131	36 (157.6 N/25mm)
<b>Elongation</b> (% at break) PSTC-131	3
<b>Total Thickness</b> (mils) PSTC-133	6 (0.15mm)
<b>Quick Stick</b> (oz/in of width) PSTC-5	
To Kraft	11 (3 N/25mm)
To Steel	25 (6.8 N/25mm)
<b>Operating Temperature Range</b>	+40°F~+225°F (+4°C~+107°C)
<b>Color</b>	Tan

