

538

BLEACHED PREMIUM KRAFT FLATBACK TAPE

DESCRIPTION

High performance, water resistant, carton sealing, bleached kraft flatback pressure-sensitive natural/synthetic backing with rubber adhesive tape. Features easy release from roll, good quick-stick, excellent bonding to carton and good edge tear resistance. Performs well as a low temperature splicing tape. **Product is not repulpable.**

PRODUCT APPLICATIONS

Carton sealing, military packaging, splicing, tabbing and light sandblasting.

GOVERNMENT COMPLIANCE

Approved as packaging tape by U. S. Postal Service and U.P.S (United Postal Service).

ASTM D-5486, Type V

PPP-T-76C, Type V

A-A-1683, Type V



intertape polymer group™

3647 Cortez Road West | Bradenton, FL 34210 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 08/12

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Kraft Flatback Paper
Adhesive	Natural / Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-1	70 (19.2 N/25mm)
Tensile Strength (lbs/in of width) MD PSTC-31	47.5 (208 N/25mm) 32 (140 N/25mm) CD
Elongation (at break)	4%
Total Thickness (mils) PSTC-33	8.0 (0.20mm)
Operating Temperature Range	+32°F ~ +180°F (0°C ~ +82°C)
Color	Natural

