

PS8

HIGH TEMP PREMIUM PAPER FLATBACK TAPE

DESCRIPTION

Strong, natural colored saturated kraft flatback paper with temperature resistant acrylic adhesive. Product is not repulpable. Temperature resistant.

PRODUCT APPLICATION

For splicing of light floor covering and similar materials during manufacturing. Also for leasing / beaming synthetic fibers.

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Saturated Flatback Paper
Adhesive	Solvent Acrylic
Tensile Strength (lbs/in width) ASTM D-3759	54 (236 N/25mm) MD 32 (140 N/25mm) CD
Elongation (% at break) ASTM D-3759	4
Adhesion to Steel (oz/in width) ASTM D-3330	54 (15 N/25 mm)
Total Thickness (mil) ASTM D-3652	9.1 (0.23 mm)
Color	Beige



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 03/11

