

Electro Tape offers a complete line of PVC vinyl electrical tapes suitable for a broad range of environments and applications. All of our vinyl tapes are constructed with a conformable, strong backing and carry a high quality, blended natural rubber adhesive. Premium grade products are achieved through increased thickness and enhanced elasticity which provide for stronger, tighter hold when wrapped and greater durability. Additional material changes to the adhesive system and vinyl film provide for tapes that remain flexible, elastic and tacky even when exposed to climate extremes. Premium grades provide superior protection when used as a jacketing for low and high voltage cable splices and repairs.

All of our vinyl electrical tapes meet UL510 requirements and CSA 22.2 approval. Our premium products (103, 750, and 850) are low lead and flame retardant.



### 850 – 8.5 mil Premium Grade Vinyl

- High Quality 8.5 mil black electrical tape.
- Resists: UV rays, acids, alkalis, abrasion, moisture, and corrosion.
- Suitable for cold and hot environments.
- Broad Temperature range: -18°C to 105°C
- **Meets ASTM D-3005 and MIL-I-24391C specifications.**
- Wound on 1.5" ID core.

### 750 – 7 mil Premium Grade Vinyl

- Cold and heat resistant – suitable for all climates. Resists: UV rays, acids, alkalis, abrasion, moisture, and corrosion.
- Tape maintains tensile strength, adhesion and integrity over Broad Temperature range: -18°C to 105°C
- Best all-around vinyl for primary electrical insulation for wire and cable splices rated up to 600 volts.
- **Meets ASTM D-3005 and HHI-595 specifications.**
- Wound on 1.5" ID core. 1" ID core available by special order on 3/4" x 66 ft only.
- Also available in 108ft length.



Series	Product Code	Size	Units/Case	Pack	Features
<b>850</b> ✂	1085207-1064	3/4" (19 mm) x 20 ft	64 / case	cello	Tape maintains elasticity, tensile strength, adhesion and integrity over broad temperature range – even in extreme cold weather.
	1085220-1024	2" (50 mm) x 20 ft	24 / case	cello	
	108507-3648	3/4" (19 mm) x 66 ft	48 / case	cello / label / plastic container	
	108507-0100	3/4" (19 mm) x 66 ft	100 / case	cello / label	High stretch and rebound nature provides moisture-tight electrical and mechanical protection.
	108507-1100	3/4" (19 mm) x 66 ft	100 / case	cello	
	108507-6100	3/4" (19 mm) x 66 ft	100 / case	bulk	
	108510-6048	1" (25 mm) x 66 ft	48 / case	bulk	
	108520-6024	2" (48 mm) x 66 ft	24 / case	bulk	
	1085807-6064	3/4" (19 mm) x 108 ft	64 / case	bulk	
	1085820-6024	2" (50 mm) x 108 ft	24 / case	bulk	
<b>750</b> ✂	1075207-1064	3/4" (19 mm) x 20 ft	64 / case	cello	High Quality 7.0 mil Black electrical tape with high rebound nature to provide moisture-tight electrical and mechanical protection.
	1075220-1024	2" (50 mm) x 20 ft	48 / case	cello	
	107507-3648	3/4" (19 mm) x 66 ft	48 / case	cello / label / plastic container	
	107507-0100	3/4" (19 mm) x 66 ft	100 / case	cello / label	Superior for harnessing of wires and cables. Often used in conjunction with our rubber tapes as a protective outer jacketing wrap.
	107507-1100	3/4" (19 mm) x 66 ft	100 / case	cello	
	107507-6100	3/4" (19 mm) x 66 ft	100 / case	bulk	
	107510-6048	1" (25 mm) x 66 ft	48 / case	bulk	
	107515-6032	1 1/2" (38mm) x 66 ft	32 / case	bulk	
107520-6024	2" (48 mm) x 66 ft	24 / case	bulk		