

TECHNICAL DATA

TYPICAL APPLICATIONS

- > For use on a variety of smooth substrates as a printed or unprinted general purpose tape
- > Packaging, bundling, binding
- > Holding, splicing, banding
- > Labeling, color coding, decorating, identification

ADVANTAGES AND BENEFITS

- > Printable and flexible
- > Adhesive system designed for excellent performance and adhesion to a variety of smooth substrates
- > Resists water, solvents and oil

CONSTRUCTION

Overall Grade/Function: Premium Grade, Printable,
General Purpose

Backing: Colored crepe paper

Adhesive: Rubber-based adhesive

COLOR(S)

	Black (BLK)		Pink (PNK)		White (WHI)
	Blue (BLU)		Gray (GRY)		Red (RED)
	Green (GRN)		Orange (ORG)		Light Blue (LBL)
	Purple (PRP)		Yellow (YEL)		Light Green (LGR)

STANDARD WIDTH(S)

9 mm 12 mm 18 mm 24 mm 48mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	23 lbs/in width	40.3 N/10mm
Adhesion to Stainless Steel	40 oz/in width	4.38 N/10mm
Thickness	6.4 mils	0.16 mm
Elongation	9 %	9 %
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D6123/D6123M-07, Type 1

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

