



PRODUCT DESCRIPTION

Liner:	60 lb bleached super calendered kraft, silicone coated both sides
Liner Side Adhesive:	Rubber
Carrier:	1.0 mil polyester film
Air Side Adhesive:	Rubber

APPLICATIONS

- Mounting Tape: foams and plastic
- Hang Tags
- POP Displays

FEATURES AND BENEFITS

- High peel and tack adhesive for demanding applications
- Product maintains its bond strength over a wide temperature range
- Dimensionally stable liner and excellent die cut ability

PHYSICAL PROPERTIES

	Standard UOM	Metric UOM	Test Method
Adhesive Thickness (Air Side)	2.2 mils	56 microns	PSTC 133
Adhesive Thickness (Liner Side)	2.2 mils	56 microns	PSTC 133
Carrier Thickness	1.0 mils	25 microns	PSTC 133
Liner Thickness	3.5 mils	89 microns	PSTC 133
Adhesion Steel (Air Side)	160 oz/in	1744 N/m	PSTC 101 Mod
Adhesion Steel (Liner Side)	160 oz/in	1744 N/m	PSTC 101 Mod
Shear Strength (Air Side)	168+ hours		PSTC 107
Shear Strength (Liner Side)	168+ hours		PSTC 107

Recommended Storage Conditions: 40-60% Humidity, 60°F - 80°F

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.