



PRODUCT DESCRIPTION

Liner:	80 lb super calendered release liner with differential release
Liner Side Adhesive:	Acrylic
Carrier:	0.5 mil polyester film
Air Side Adhesive:	Rubber

APPLICATIONS

- Laminating: paper, plastic, foam, and metal
- General Purpose Mounting and Assembly
- Packaging Applications

FEATURES AND BENEFITS

- Low peel acrylic adhesive on the liner side is designed for easy removal with no residue
- Rubber adhesive on the air side has excellent adhesion to PE and other low surface energy materials

PHYSICAL PROPERTIES

	Standard UOM	Metric UOM	Test Method
Adhesive Thickness (Air Side)	1.7 mils	43 microns	PSTC 133
Adhesive Thickness (Liner Side)	0.8 mils	20 microns	PSTC 133
Carrier Thickness	0.5 mils	13 microns	PSTC 133
Liner Thickness	4.8 mils	122 microns	PSTC 133
Adhesion Steel (Air Side)	75 oz/in	818 N/m	PSTC 101 Mod
Adhesion Steel (Liner Side)	19 oz/in	207 N/m	PSTC 101 Mod
Shear Strength (Air Side)	> 168 hours		ASTM D3654 Mod
Shear Strength (Liner Side)	40 hours		ASTM D3654 Mod

Recommended Storage Conditions: 40-60% Humidity, 60°F - 80°F

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.