



PRODUCT DESCRIPTION

Liner:	120 lb Natural polycoated kraft, silicone coated on both sides
Liner Side Adhesive:	Acrylic
Carrier:	0.5 mil polyester film
Air Side Adhesive:	Acrylic

APPLICATIONS

- Laminating: paper, plastic, foam, and metal
- Mounting Tape: removable

FEATURES AND BENEFITS

- The liner side adhesive is a low peel acrylic designed for clean removability from a variety of surfaces.
- The air side adhesive is a permanent acrylic with good adhesive to a variety of surfaces.

PHYSICAL PROPERTIES

	Standard UOM	Metric UOM	Test Method
Adhesive Thickness (Air Side)	1.7 mils	43 microns	PSTC 133
Adhesive Thickness (Liner Side)	1.0 mils	25 microns	PSTC 133
Carrier Thickness	0.5 mils	13 microns	PSTC 133
Liner Thickness	10.0 mils	254 microns	PSTC 133
Adhesion Steel (Air Side)	56 oz/in	610 N/m	PSTC 101 Mod
Adhesion Steel (Liner Side)	18 oz/in	196 N/m	PSTC 101 Mod
Shear Strength (Air Side)	100+ hours		PSTC 107
Shear Strength (Liner Side)	100+ hours		PSTC 107
Application Temperature	50°F to 150°F	10°C to 65°C	
Laminating Temperature	50°F to 150°F	10°C to 65°C	
Maximum Continuous Use	180°F	82°C	
Intermittent Use	200°F	93°C	

Recommended Storage Conditions: 40-60% Humidity, 60°F - 80°F

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.