



### PRODUCT DESCRIPTION

<b>Liner:</b>	Kraft Liner: 60 lb or 80 lb Board: 8 pt or 12 pt
<b>Liner Side Adhesive:</b>	Acrylic
<b>Carrier:</b>	0.5 mil polyester film
<b>Air Side Adhesive:</b>	Acrylic

### APPLICATIONS

- Laminating: paper, felt, sponge rubber, foam and plastic
- General Purpose Mounting Tape

### FEATURES AND BENEFITS

- Adhesive bonds well to most ether and ester polyurethane foams, closed and open cell sponge rubber, and most metal and plastics.
- Specifically designed for application where balanced peel and shear is necessary.
- Available on different liners. The liner options are a 60 lb or 80 lb kraft liner or an 8 pt or 12 pt board

### PHYSICAL PROPERTIES

	Standard UOM	Metric UOM	Test Method
Adhesive Thickness (Air Side)	1.5 mils	38 microns	PSTC 133
Adhesive Thickness (Liner Side)	1.2 mils	30 microns	PSTC 133
Carrier Thickness	0.5 mils	13 microns	PSTC 133
Adhesion Steel (Air Side)	80 oz/in	872 N/m	PSTC 101 Mod
Adhesion Steel (Liner Side)	80 oz/in	872 N/m	PSTC 101 Mod
Application Temperature	50°F to 150°F	10°C to 65°C	
Operating Temperature	-34°F to 225°F	-37°C to 107°C	

Recommended Storage Conditions: 40-60% Humidity, 60°F - 80°F

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.