

592

6.0 MIL MEDIUM GRADE DOUBLE-COATED PAPER TAPE

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

A beige crepe paper tape coated on both sides with an aggressive, pressure-sensitive natural rubber adhesive that bonds equally well on both sides to almost any surface. Features a an easy release treated white crepe liner. Product is not re-pulpable.

PRODUCT APPLICATION

Photograph mounting, carpet installation, steel-rule die (make ready), textile manufacturing (twister room), printing industry, and any application that requires the joining of two surfaces.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Crepe Paper
Adhesive	Natural Rubber/Resin
Adhesion to Steel (oz/in of width) PSTC-1	47 (12.8 N/25mm)
Tensile Strength (lbs/in of width) PSTC-31	23 (101 N/25mm)
Elongation (at break) PSTC-31	8.5%
Total Thickness (mils) With liner	10.4 (0.26mm)
Without liner	6.0 (0.15mm)
Quick Stick To Steel (oz/in of width) PSTC-5	20 (5.5 N/25mm)
Color	Beige



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/10

