

## TECHNICAL DATA

## TYPICAL APPLICATIONS

- > Use printed or unprinted on a variety of substrates for general purpose packaging, bundling, holding, binding, splicing, labeling, color coding, banding, decorating and identification

## ADVANTAGES AND BENEFITS

- > Excellent printability
- > Adhesive system designed for excellent performance and adhesion to a variety of substrates
- > Flexible
- > Resists oil and staining
- > Available in converter-size rolls


## CONSTRUCTION

Overall Grade/Function: Premium Grade

Backing: flatback paper

Adhesive: Moderate tack, blended rubber-based adhesive

## COLOR(S)



## STANDARD WIDTH(S)

18 mm    24 mm    48 mm

## STANDARD LENGTH(S)

55 mm

Contact your Shurtape sales representative for other available sizes.

## PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	29 lbs/in width	50.8 N/10 mm
Adhesion to Stainless Steel	45 oz/in width	4.93 N/10 mm
Thickness	5.5 mils	0.14 mm
Elongation	3 %	3 %
Service Temperature Range	32 F to 150 F	0 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

## APPLICABLE STANDARDS

ASTM D6123/D6123M-07 Type II

## STORAGE &amp; USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.